

PAL Specifications

Technical:

- Lifting Capacity: 300 lb
- Lifting: Linak LA34 Mechanical Actuator
- Max. Thrust: 1680 lb
- Voltage: 24 VDC
- Max. Amp: 9
- Max. Speed: 0.59 inch/sec.
- Rotation: ITT SWMK 403.033 24 VDC 13 RPM
- Gearing Ratio 9:1
- Power: Linak Battery Pack BAJ1 24 VDC, IP65 Gel Lead Acid

Materials & Finish:

- Arms: Powder Coated Aluminum
- Mast: Powder Coated, Stainless Steel
- Handle: Powder Coated Aluminum
- Housing: Vacuum Formed ABS Plastic

Casters:

- Front: Tente 8477 Precision Ball Bearing, Stainless Steel, 5" total lock swivel
- Rear: Tente 5328 Precision Ball Bearing, Stainless Steel, 5" fixed Polyurethane Tread

Dimensions:

- Weight: 850 lb
- Overall Height: 72. in
- Base Height: 23.5 in
- Base Length: 36 in
- Base Width: 29.25 in
- Clearance: 1.25" with stabilizer, 2" without stabilizer
- Overall Length (foot print): 81.5" fully extended w/o footrest, 95.5" with footrest
55" in stored position

Range of Motion:

- Lifting:
 - Variable to suit needs of pool
 - 49" total travel
 - Seat Depth: 18-20" below water line
- Rotational: 240° total rotation, 120° from each side