

Drive Full Electric Low Height Bed

HCPCS: E0297



- Low Deck height with flexibility to configure "roll at any height" or "roll at low height only" castor location (Figure A)
- -Roll at any Height: 11 1/2" (290mm) to 22 7/8" (580 mm) deck height
- -Roll at Low Height: 9 1/2" (241 mm) to 19 7/8" (505mm) deck height
- Quiet, convenient, full electric operation provides smooth position change w/easy-to-use Hand Pendant control of Head/Foot Section positioning and overall height of the bed frame for maximum comfort and versatility for the patient or caregiver (Figure B)
- Height-adjustment and Head/Foot deck motors come pre-installed on the foot section no assembly required
- In the event of power failure, top mounted Hi/Lo crank accessibility (Figure C)
- Easy-to-transport and set up Bed ships in two cartons
- Channel frame construction provides superior strength and reduced weight
- Reinforced frame resists twisting and bending
- Long lasting Zinc-coated spring deck for Patient comfort
- Heavy-duty bed ends attractive, easy-to-maintain
- Headboard is taller than footboard to blend with home décor, wood grain panels are break and scratch resistant (Figure D)
- Labels and color-coded springs help ensure accurate installation of side rails for patient safety (Figure E)
- High performance workhorse muscle of the 3-motor power plant is an industry standard (Figure F)
- Half rails and full rails available (Sold separately)
- Motor is UL Approved, Manufactured in ISO9001 facility
- Bed, side rails and mattress safety-tested by SGS, a nationally recognized testing facility
- Satisfies all applicable FDA entrapment guidelines
- Extension kit available (model #15005EXTKIT-L) extends length from 80" to 84"
- Weight Capacity 450 lbs
- Includes occupant, mattress, rails, trapeze, accessories, personal affects, etc.

PRODUCTS	Description
15005L	Drive Full Electric Low Height Bed, EA
15005LBV-FR	Drive Full Electric Low Height Bed, EA
15005LBV-HR	Drive Full Electric Low Height Bed, EA
15005LBV-PKG	Drive Full Electric Low Height Bed, EA
15005LBV-PKG-1	Drive Full Electric Low Height Bed, EA
15005LBV-PKG-1-T	Drive Full Electric Low Height Bed, EA
15005LBV-PKG-2	Drive Full Electric Low Height Bed, EA
15005LBV-PKG-T	Drive Full Electric Low Height Bed, EA

SPECIFICATIONS	Description
Carton Shipping Weight	198 lbs
Roll at Low Height	9.5" (241mm) to 19.78" (505mm) deck height

SPECIFICATIONS	Description
Roll at any Height	11.5" (290mm) to 22.78" (580 mm) deck height
Unit Dimensions	36" (W) x 88" (L)
Warranty	Lifetime on welds, 5 year on frame and motor, 1 year on all other parts and components
Weight	185 lbs
Weight Capacity	204 kg/ 450 lbs (Includes occupant, mattress, side rails, trapeze, accessories, personal affects, etc.)
PARTS	Description
15547F-FP-1	Foot Board Panel, 15235, Delta Bed, 1/ea, CS
15547H-HP-1	HeadBoardPanel,15235/15547H,DeltaBed,1ea, CS
15215-15008	
15216-15013-L	
15005P1029-L	Hi-Lo Mounting Bracket, Linak Motor, CS
15005HLC-L	HiLoMotor/JBoxCableLinak15005,1ea, CS
15005HL-L	HiLoMotorLinak15005,1ea, CS
15005JBN-L	JunctionBoxLinak15005,1ea, CS
15005HCN-L	HandControlLinak15005,1ea, CS
15005P-1028	Quick Release for Bed Motor,1/ea, CS
15005P1016	Cotter Pin,Semi,Full,1/ea, CS
15013-L	LinakFootSpring15005,1ea, CS
15033MHLNC	HI-LO Motor Connector for 15033MHL, 1/ea, CS
15547H-F	Head&Footboard15235Delta,15005L,1/set, CS
15547-CRANK	Hand Crank,Delta Beds,1ea, CS
15030P-1001	Bushing,Plastic, for caster,1/ea, CS
15547H	Head Board,15235,Delta Bed,1ea, CS
15547H-PF	HeadBoardPanelFrame15235DeltaBed,1ea, CS
15547F	Foot Board,15235,Delta Bed,1ea, CS
15547F-PF	FootBoardPanelFrame15235DeltaBed,1ea, CS